

Time delay relays

10 Amps

Series	M83726/28,29,30,31
Rating	10 Amps
觸點配置	2 PDT
電性資料(VAC with 400 Hz)	
Timing range	0.1 – 600 seconds
Recycle time, max.	50 ms
Input & control Volt	20 – 30 VDC
Operating current max	150 mAmps
Sea level	1000 / 60 Hz
80,000 ft	350 / 60 Hz
絕緣阻抗	1000 megaOhms @ 500 VDC
Environmental data	
Temperature range	-55°C - 125°C
Mechanical data	
Weight, max	71 g
Dimensions, max (in)	1.025 * 1.025 * 1.010

Solid-state time delay relays

150 – 250 mAmps

Series	M83726/24,25	M83726/20,21	M83726/22
Rating	150 mAmps	250 mAmps	
觸點配置	SPST		
電性資料(VAC with 400 Hz)			
Timing range	0.05 - 500		1 cycle / min. to 10 cycles / second
Recycle time, max.	10 ms		
Input & control Volt	20 – 32 VDC	18 – 32 VDC	
Operating current max	10 mAmps	5 mAmps + load	
Sea level	1000 / 60 Hz		
80,000 ft	-	350 / 60 Hz	
絕緣阻抗	1000 megaOhms @ 500 VDC		
Environmental data			
Temperature range	-55°C - 125°C		
Mechanical data			
Weight, max	16 g	14 g	14 g
Dimensions, max (in)	.81 * .41 * .31		

